

# AIR OPERATED DOUBLE DIAPHRAGM PUMPS

NEW OIL

IDEAL FOR TRANSFER OF NEW OIL, WASTE OIL, ANTIFREEZE AND WINDSHIELD FLUID.

MAXIMUM WORKING

PRESSURE 6,3 BAR – 100 PSI

PRESSURE RATIO : 1:1

POLYPROPYLENE BODY AND DIAPHRAGMS IN BUNA-N



NP 1050

NEW



NP 1051

NEW

		NP 1050	NP 1051	NP 1052
RATIO A 6 BAR	liter/min.	26	53	132
	gallon/min	6,8	14	35
PRESSURE WORKING	BAR	3 - 6,3	3 - 6,3	3 - 6,3
PRESSURE WORKING	PSI	42 - 90	42 - 90	42 - 90
AIR INLET	ET	1/4"	3/8"	3/8"
PLUG OUTLET		3/8"	1/2"	1"
NOISE	dB	78	78	78
AIR CONSUMPTION	l/min.	150	450	1130
WEIGHT	KG	1,4	4,5	10,90
SHIPPING DIMENSIONS	mm	160x160x130	270x210x330	—

NP 1052

AS ITEM NP 1051  
BUT INLET 1"

NEW

\* Contact us for special uses